

# RLB452

## ULTRA PREMIUM OPEN SHOULDER DRIVE-POSITION TIRE

- Robust casing design with stone ejectors preserves the casing, maximizing service life.
- Offset shoulder blocks with ties keep the tread stable, providing long tread life.
- Deep original tread for higher removal mileage.

**EXPLORE**



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	DUAL MAX LOAD/PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT	TYPE
1133621255	11R22.5	14	G	144/142	L	41.9	11.1	28	8.25	6175lb/105psi	5840lb/105psi	19.6	496	129lb/58kg	TL
1133621256	11R22.5	16	H	148/145	L	41.9	11.1	28	8.25	6940lb/123psi	6390lb/123psi	19.6	496	132lb/60kg	TL
1133629255	295/75R22.5	14	G	144/141	L	41.1	11.9	28	9.00	6175lb/110psi	5675lb/110psi	19.3	505	131lb/59kg	TL
1133629257	295/75R22.5	16	H	146/143	J	41.1	11.9	28	9.00	6610lb/120psi	6005lb/120psi	19.2	506	131lb/59kg	TL
1133621455	11R24.5	14	G	146/143	L	43.6	10.9	28	8.25	6610lb/105psi	6005lb/105psi	20.1	476	138lb/62kg	TL
1133621456	11R24.5	16	H	149/146	L	43.6	10.9	28	8.25	7160lb/120psi	6610lb/120psi	20.1	476	141lb/64kg	TL
1133628455	285/75R24.5	14	G	144/141	L	41.2	10.9	28	8.25	6175lb/110psi	5675lb/110psi	19.6	493	131lb/59kg	TL
1133628457	285/75R24.5	16	H	147/144	K	41.2	10.9	28	8.25	6780lb/120psi	6175lb/120psi	19.6	493	131lb/59kg	TL