

# RLB1

## PREMIUM OPEN SHOULDER DRIVE-POSITION TIRE

- Open shoulder design with locking center rib provides a blend of long wear and traction in any environment.
- Tie bar on the outside shoulder helps to maintain stability of the footprint and combat irregular wear.
- Siping in the tread blocks allows the tire to cut through water and debris.
- Robust design provides protection from hazards and job site debris.

**EXPLORE**



| PRODUCT CODE | TIRE SIZE   | PLY RATING | LOAD RANGE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAM. (IN) | SECTION WIDTH (IN) | TREAD DEPTH (32NDS) | RIM  | SINGLE MAX LOAD/PRESSURE | DUAL MAX LOAD/PRESSURE | STATIC LOAD RADIUS | REVS PER MILE | WEIGHT     | TYPE |
|--------------|-------------|------------|------------|------------|--------------|--------------------|--------------------|---------------------|------|--------------------------|------------------------|--------------------|---------------|------------|------|
| 1133411255   | 11R22.5     | 14         | G          | 144/142    | M            | 41.7               | 10.9               | 26                  | 8.25 | 6175lb/105psi            | 5840lb/105psi          | 19.8               | 493           | 126lb/57kg | TL   |
| 1133411256   | 11R22.5     | 16         | H          | 148/145    | M            | 41.7               | 10.9               | 26                  | 8.25 | 6940lb/123psi            | 6390lb/123psi          | 19.8               | 493           | 130lb/59kg | TL   |
| 1133419255   | 295/75R22.5 | 14         | G          | 144/141    | L            | 40.9               | 11.7               | 26                  | 9.00 | 6175lb/110psi            | 5675lb/110psi          | 19.4               | 498           | 131lb/59kg | TL   |
| 1133411455   | 11R24.5     | 14         | G          | 146/143    | L            | 43.7               | 10.9               | 26                  | 8.25 | 6610lb/105psi            | 6005lb/105psi          | 21.0               | 471           | 138lb/62kg | TL   |
| 1133411456   | 11R24.5     | 16         | H          | 149/146    | L            | 43.7               | 10.9               | 26                  | 8.25 | 7160lb/120psi            | 6610lb/120psi          | 21.0               | 471           | 142lb/64kg | TL   |
| 1133418455   | 285/75R24.5 | 14         | G          | 144/141    | L            | 41.9               | 11.0               | 26                  | 8.25 | 6175lb/110psi            | 5675lb/110psi          | 19.8               | 485           | 135lb/61kg | TL   |
| 1133412796   | 225/70R19.5 | 14         | G          | 128/126    | N            | 32.5               | 8.8                | 19                  | 6.75 | 3970lb/110psi            | 3750lb/110psi          | 15.1               | 644           | 71lb/32kg  | TL   |
| 1133414796   | 245/70R19.5 | 16         | H          | 136/134    | J            | 33.5               | 9.6                | 19                  | 7.50 | 4940lb/120psi            | 4675lb/120psi          | 15.2               | 617           | 85lb/39kg  | TL   |
| 1133419206   | 9.00R20     | 16         | H          | 144/142    | L            | 40.6               | 10.1               | 26                  | 7.00 | 6175lb/130psi            | 5840lb/130psi          | 19.1               | 505           | 114lb/51kg | TT   |
| 1133411026   | 10.00R20    | 16         | H          | 146/143    | L            | 41.5               | 10.7               | 22                  | 7.50 | 6610lb/120psi            | 6005lb/120psi          | 19.4               | 497           | 135lb/61kg | TT   |
| 1133410225   | 10R22.5     | 14         | G          | 141/139    | K            | 40.2               | 10.0               | 22                  | 7.50 | 5675lb/115psi            | 5355lb/115psi          | 18.3               | 512           | 112lb/50kg | TL   |
| 1133415726   | 255/70R22.5 | 16         | H          | 140/137    | K            | 36.7               | 9.9                | 22                  | 7.50 | 5510lb/120psi            | 5070lb/120psi          | 17.4               | 560           | 98lb/44kg  | TL   |
| 1133419258   | 295/80R22.5 | 18         | J          | 152/149    | M            | 41.5               | 11.7               | 26                  | 9.00 | 7830lb/130psi            | 7160lb/130psi          | 19.8               | 493           | 139lb/63kg | TL   |