

FR610



OptiGreen Series

ULTRA PREMIUM FUEL EFFICIENT STEER-POSITION TIRE

- New OptiGreen compound delivers low rolling resistance and maximum fuel efficiency.
- Innovative siping and defense grooves for long even wear.
- Durable casing construction resists fatigue and delivers industry-leading lower total cost of ownership.
- Micro siping throughout the tread delivers improved traction and stability.

EXPLORE



| PRODUCT CODE | TIRE SIZE | PLY RATING | LOAD RANGE | LOAD INDEX | SPEED SYMBOL | OVERALL DIAM. (IN) | SECTION WIDTH (IN) | TREAD DEPTH (32NDS) | RIM | SINGLE MAX LOAD/PRESSURE | DUAL MAX LOAD/PRESSURE | STATIC LOAD RADIUS | REVS PER MILE | WEIGHT | TYPE |
|--------------|-------------|------------|------------|------------|--------------|--------------------|--------------------|---------------------|------|--------------------------|------------------------|--------------------|---------------|------------|------|
| 1133781255 | 11R22.5 | 14 | G | 144/142 | L | 41.4 | 11.0 | 20 | 8.25 | 6175lb/105psi | 5840lb/105psi | 19.4 | 500 | 119lb/54kg | TL |
| 1133781256 | 11R22.5 | 16 | H | 148/145 | L | 41.4 | 11.0 | 20 | 8.25 | 6940lb/123psi | 6390lb/123psi | 19.4 | 500 | 124lb/56kg | TL |
| 1133789255 | 295/75R22.5 | 14 | G | 144/141 | L | 40.3 | 11.7 | 20 | 9.00 | 6175lb/110psi | 5675lb/110psi | 18.8 | 516 | 121lb/55kg | TL |
| 1133789256 | 295/75R22.5 | 16 | H | 146/143 | L | 40.3 | 11.7 | 20 | 9.00 | 6610lb/120psi | 6005lb/120psi | 18.8 | 516 | 125lb/57kg | TL |
| 1133781455 | 11R24.5 | 14 | G | 146/143 | L | 43.2 | 10.9 | 20 | 8.25 | 6610lb/105psi | 6005lb/105psi | 20.1 | 480 | 125lb/57kg | TL |
| 1133781456 | 11R24.5 | 16 | H | 149/146 | L | 43.2 | 10.9 | 20 | 8.25 | 7160lb/120psi | 6610lb/120psi | 20.1 | 480 | 128lb/58kg | TL |
| 1133788455 | 285/75R24.5 | 14 | G | 144/141 | L | 41.5 | 10.9 | 20 | 8.25 | 6175lb/110psi | 5675lb/110psi | 19.5 | 501 | 122lb/55kg | TL |