

REM-9



(E4) HAULAGE TIRE

The Double Coin REM-9 OTR radial design offers special compounds to withstand severe mining applications, extend tire life and promote long-term retreadability. The REM-9 OTR tire is designed with a non-directional center rib tread pattern for enhanced off-the-road traction. Its deep tread depth also provides extended tread life in a wide variety of conditions.

EXPLORE



PRODUCT CODE	TIRE SIZE	PATTERN	LOAD SYMBOL	SPEED MAX (KM/H)	SPEED MAX (MPH)	OVERALL DIAMETER (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	WEIGHT	TYPE
1087206252	26.5R25	REM-9 (A)	★★	50	30	70	27	69	22.00/3.0	25300lb/76psi	1191lb/540kg	TL
1087206253	26.5R25	REM-9 (S)	★★	50	30	70	27	69	22.00/3.0	25300lb/76psi	1191lb/540kg	TL
1087206254	26.5R25	REM-9 (B)	★★	50	30	70	27	69	22.00/3.0	25300lb/76psi	1191lb/540kg	TL
1087202955	29.5R25	REM-9 (A)	★★	50	30	75	30	76	25.00/3.5	30800lb/76psi	1434lb/650kg	TL
1087202956	29.5R25	REM-9 (S)	★★	50	30	75	30	76	25.00/3.5	30800lb/76psi	1434lb/650kg	TL
1087202957	29.5R25	REM-9 (B)	★★	50	30	75	30	76	25.00/3.5	30800lb/76psi	1434lb/650kg	TL

* Compounds: **A** cut/chip; **S** standard; **B** heat