

# RR99



## PREMIUM ON/OFF HIGHWAY MIXED SERVICE ALL-POSITION TIRE

- Strong all-position tread pattern designed for multiple on/off highway uses.
- Outside shoulder grooves with zigzag center grooves provide added traction in mud and soft soil.

**EXPLORE**



PRODUCT CODE	TIRE SIZE	PLY RATING	LOAD RANGE	LOAD INDEX	SPEED SYMBOL	OVERALL DIAM. (IN)	SECTION WIDTH (IN)	TREAD DEPTH (32NDS)	RIM	SINGLE MAX LOAD/PRESSURE	DUAL MAX LOAD/PRESSURE	STATIC LOAD RADIUS	REVS PER MILE	WEIGHT	TYPE
1133437565	7.50R16	14	G	122/118	L	31.9	8.3	16	6.00	3305lb/112psi	2910lb/112psi	14.7	656	59lb/27kg	TT
1133991256	11R22.5	16	H	148/145	L	41.3	10.9	19	8.25	6940lb/123psi	6390lb/123psi	19.5	496	124lb/56kg	TL
1133991456	11R24.5	16	H	149/146	L	43.4	10.9	21	8.25	7160lb/120psi	6610lb/120psi	21	484	131lb/59kg	TL
1133992256	12R22.5	16	H	152/148	L	42.7	11.8	21	9.00	7830lb/120psi	6940lb/120psi	20.1	516	135lb/61kg	TL
1133992258	12R22.5	18	J	152/149	L	42.7	11.8	21	9.00	7830lb/61psi	7160lb/61psi	20.1	516	135lb/61kg	TL
1133433227	13R22.5	18	J	154/151	M	43.9	12.2	20	9.75	8270lb/123psi	7610lb/123psi	20.7	465	164lb/74kg	TL
1133991257	315/80R22.5	18	J	156/152	L	42.7	12.4	19	9.00	8820lb/120psi	7830lb/120psi	19.9	484	146lb/66kg	TL
1133991258	315/80R22.5	20	L	157/154	L	42.4	12.2	19	9.00	9090lb/130psi	8270lb/130psi	19.9	483	148lb/67kg	TL
1133991259	315/80R22.5	22	M	160/157	65MPH	42.4	12.2	20	9.00	10000lb/130psi	9090lb/130psi	19.9	483	149lb/67kg	TL
1133439205	9.00R20	14	G	141/139	M	40.2	10.1	19	7.00	5675lb/115psi	5355lb/115psi	18.9	510	111lb/50kg	TT