

REM-28S



(L3/G3/MCS) LOADER/GRADER/ MOBILE CRANE SERVICE TIRE

The REM-28S is designed with a universal tread pattern for increased traction and performance in winter conditions. Its multiple application use includes loader, grader and on-highway, high speed mobile crane wheel positions.

★★★ Star product DOT certified for on-highway use



| PRODUCT CODE | TIRE SIZE | PATTERN | LOAD SYMBOL | SPEED MAX (KM/H) | SPEED MAX (MPH) | OVERALL DIAMETER (INCH) | SECTION WIDTH (INCH) | TREAD DEPTH (32NDS) | RIM | SINGLE MAX LOAD/PRESSURE | TIRE WEIGHT | TIRE TYPE |
|--------------|-------------------------|---------|-------------|------------------|-----------------|-------------------------|----------------------|---------------------|-----------|--------------------------|-------------|-----------|
| 1107308951 | 14.00R24 (385/95R24) | REM-28S | ★★ | 50 | 30 | 54 | 16 | 31 | 10.00 | 12320lb/101psi | 294lb/133kg | TL |
| 1117208952 | 14.00R25 (385/95R25) | REM-28S | ★★★ | 70 | 43 | 54 | 16 | 31 | 10.00/1.5 | 13948lb/144psi | 298lb/135kg | TL |
| 1107300251 | 17.5R25 | REM-28S | ★★ | 50 | 30 | 53 | 18 | 34 | 14.00/1.5 | 11990lb/76psi | 336lb/152kg | TL |
| 1107300251 | 17.5R25 | REM-28S | ★★ | 10 | 5 | 53 | 18 | 34 | 14.00/1.5 | 18700lb/94psi | 336lb/152kg | TL |
| 1107300751 | 20.5R25 | REM-28S | ★★ | 50 | 30 | 58 | 21 | 39 | 17.00/2.0 | 16060lb/76psi | 510lb/231kg | TL |
| 1107300751 | 20.5R25 | REM-28S | ★★ | 10 | 5 | 58 | 21 | 39 | 17.00/2.0 | 25300lb/94psi | 510lb/231kg | TL |
| 1107303251 | 23.5R25 | REM-28S | ★★ | 50 | 30 | 64 | 24 | 45 | 19.50/2.5 | 20350lb/65psi | 708lb/321kg | TL |
| 1107303251 | 23.5R25 | REM-28S | ★★ | 10 | 5 | 64 | 24 | 45 | 19.50/2.5 | 31900lb/83psi | 708lb/321kg | TL |